

BPG 7829



PROPERTIES

BPG 7829 Solar Set is made of a unique combination of next-generation engineered components in an innovative configuration to withstand the harsh requirements in molten salt applications. The special bottom ring protects the sealing set against aggressive or oxidising media, while the top of the set is additionally equipped with a metal cap to protect the set against the atmosphere. The core of the set features an advanced sealing material composition supported by intermediate, mineral-based high-temperature barrier discs, which create a reliable low leakage sealing solution.

APPLICATIONS

BPG 7829 has been especially developed as a sealing element for high temperature and corrosive resistant valves used in molten salt applications. These high temperature valves are currently in use at Concentrating Solar Plants (CSP) where molten salts are being used as a substitute to conventional heat transfer fluids, such as heat transfer oils and steam.

OPERATION PARAMETERS

Speed	2 m/s
Temperature	-200°C...+600°C
PH Value	0 ... 14
Pressure	30 MPa

PRODUCT SPECIFICATIONS

Media	Molten salt, oxidizing media and other chemicals
-------	--

BENEFITS

- Top ring with metal cap
- Oxidation protection against atmosphere
- Engineered compound rings
- Dry lubrication at temperature and protection against media
- Mineral based discs between sealing rings
- Barrier against media permeation
- Special bottom ring
- Protection against aggressive media